

SURAT KETERANGAN

Nomor: 931/UNUSA-LPPM/Adm-I/VI/2022

Lembaga Penelitian dan Pengabdian Kepada Masyarakat (LPPM) Universitas Nahdlatul Ulama Surabaya menerangkan telah selesai melakukan pemeriksaan duplikasi dengan membandingkan artikel-artikel lain menggunakan perangkat lunak **Turnitin** pada tanggal 04 Juni 2022.

Judul : *Optimization of Touristant ASV with Jacobian Approach*
Penulis : Teguh Herlambang, Diecky Adzkiya, Hendro Nurhadi
No. Pemeriksaan : 2022.06.10.293

Dengan Hasil sebagai Berikut:

Tingkat Kesamaan diseluruh artikel (*Similarity Index*) yaitu 14%

Demikian surat keterangan ini dibuat untuk digunakan sebagaimana mestinya

Surabaya, 10 Juni 2022

Ketua LPPM,



UNUSA
LPPM

Achmad Syafiuddin, Ph.D.

NPP. 20071300

LPPM Universitas Nahdlatul Ulama Surabaya

Website : lppm.unusa.ac.id

Email : lppm@unusa.ac.id

Hotline : 0838.5706.3867

Optimization of Touristant ASV with Jacobian Approach

by Teguh Herlambang 36

Submission date: 04-Jun-2022 12:11PM (UTC+0700)

Submission ID: 1850167891

File name: 36._Paper_Jurnal_Optimization_Of_Touristant.pdf (270.32K)

Word count: 1706

Character count: 7851

OPTIMIZATION OF TOURISTANT ASV WITH JACOBIAN APPROACH

Teguh Herlambang¹, Diecky Adzkiya², , Hendro Nurhadi^{3,4}

¹Information System Department³ University of Nahdlatul Ulama Surabaya (UNUSA)
teguh@unusa.ac.id

² Department of Mathematics, FMKSD ITS, Indonesia
dieky@matematika.its.ac.id

³Department of Mechanical Engineering, Vocational Faculty, ITS, Indonesia

⁴Center of Excellence for Mechatronics Industrial Automation (PUI-PT MIA-RC)
hdnurhadi@me.its.ac.id

ABSTRACT

An Autonomous Surface Vehicle (ASV) is an unmanned ship that can automatically navigate itself in watery area. ASV can be utilized as tourism modes, transportation modes, Indonesian military (TNI) fleets or warships. In this paper, the study used a Touristant ASV prototype with a length of 3 meters, a diameter of 1.5 meters, and a height of 1.3 meters. The ASV motion system is a linear model with 3-DOF (surge, sway and yaw), resulted from the linearization of the ASV nonlinear model into a linear model which, then, was optimized as the basis of the navigation and guidance control system. The objective of this paper is to check the controllability and observability of the ASV Touristant linear model. The contribution of this paper is to provide numeric study on the controllability and observability of the model.

Keyword: ASV, 3-DOF, linear model, Optimization, Controlable, Observable

1. INTRODUCTION

Indonesia is a country with a large watery area of about two thirds of the country's total territory [1,2]. Therefore, the country requires a multifunctional vehicle that can be utilized for a transportation mode, a mode of tourism, and a maritime defense system [3]. One of the multifunctional vehicles is the Autonomous Surface Vehicle (ASV). ASV is an unmanned ship that can automatically navigate itself in the waters. Since the ASV does not have a crew on it, a control system is needed. Before the control system is simulated, the system must be optimized first to find out the nature of its controllability and observability [4].

In this paper, the study used an ASV Touristant prototype with a length of 3 meters, a diameter of 1.5 meters, and a height of 1.3 meters, and the ASV Touristant can carry 2 up to 3 people, making it quite adequate as a tourism mode or a vessel for

border areas monitoring. The model used was a linear model resulting from the linearization of the non-linear model. The linear model was hypothesized that the nature of its controllability and observability is the basis of the navigation and guidance control system.

2. MATERIAL / METHODOLOGY

2.1. Autonomous Surface Vehicle

ASV has GPS (Global Positioning System), sensors, gas, pH sensors, bluetooth, and telemetry installed. The ship automatically moves to the determined location in real-time. ASV can be used, other than as a research vessel, for a survey ship, inspection of river conditions, seismic surveys, rescue operations and the like. The profile and specifications of TOURISTANT ASV are as shown in Figure 2.1 and Table 2.1.




FIGURE 2.1. Profile of Touristant ASV

TABLE 2.1. Specification of Touristant ASV

Length	4.12 m
Beam	1.625 m
Depth	1.027 m
DWL	0.3 m
AP	-2.618 m
FP	2.618 m

The study used the equation of ship motion with 3 degrees of freedom from 6 degrees of freedom namely surge, sway and yaw. In general, the ship motions are divided into two types, that is, translational and rotational motions. Translational motion is divided into three, that is, surge, sway and heave. While rotational motion is divided into three, that is roll, pitch, and yaw [5].

By using a simplified nonlinear model [5]:

Surge

$$(m - X_{\dot{u}})\dot{u} = X_{|u|u}|u|u + (1 - h)X_{prop} + (m + X_{vr})vr +$$

Sway

$$(m - Y_{\dot{v}})\dot{v} + (mx_G - Y_{\dot{r}})\dot{r} = -(m - Y_{ur})ur + Y_{uv}uv +$$

Yaw

$$(mx_G - N_{\dot{v}})\dot{v} + (I_z - N_{\dot{r}})\dot{r} = -(mx_G - N_{ur})ur + N_{uv}uv + N_{|v|v}|v|v + N_{|r|r}|r|r + N_{\delta\delta}\delta^2 + X_{wind} + X_{waves}$$

From the above equation, what is meant

by X_{ext} , Y_{ext} and N_{ext} is external interference to the motion of surge, sway and yaw. In this

study, the external interference or environmental factors are considered as the force against wind speed and that against wave height and moment of wind speed and force against wave height. So, the equations are as follows:

$$X_{ext} = X_{wind} + X_{waves}$$

$$Y_{ext} = Y_{wind} + Y_{waves}$$

$$N_{ext} = N_{wind} + N_{waves}$$

From the description of X_{ext} , Y_{ext} and N_{ext} , nonlinear equation is obtained as follows.

Surge

$$(m - X_{\dot{u}})\dot{u} = X_{|u|u}|u|u + (1 - h)X_{prop} + (m + X_{vr})vr + (mx_G +$$

Sway

$$(m - Y_{\dot{v}})\dot{v} + (mx_G - Y_{\dot{r}})\dot{r} = -(m - Y_{ur})ur + Y_{uv}uv + Y_{|v|v}|v|v +$$

Yaw

$$(mx_G - N_{\dot{v}})\dot{v} + (I_z - N_{\dot{r}})\dot{r} = -(mx_G - N_{ur})ur + N_{uv}uv + N_{|v|v}|v|v|$$

Then supposed as follows:

$$U_{surge} = X_{|u|u}|u|u + (m + X_{vr})vr + (mx_G + X_{rr})r^2 + X_{\delta\delta}\delta^2 + X_{wind} + X_{waves} \quad (4)$$

$$V_{sway} = -(m - Y_{ur})ur + Y_{uv}uv + Y_{|v|v}|v|v + Y_{|r|r}|r|r + Y_{wind} + Y_{waves} \quad (5)$$

$$N_{yaw} = -(mx_G - N_{ur})ur + N_{uv}uv + N_{|v|v}|v|v + N_{|r|r}|r|r + N_{\delta\delta}\delta^2 + X_{wind} + N_{waves} \quad (6)$$

From the above examples of U_{surge} , V_{sway} and N_{yaw} then substituted into the equation (4 - 6), Thus,

$$(m - X_{\dot{u}})\dot{u} = (1 - h)X_{prop} + X_{|u|u}|u|u + (1 - h)X_{prop} + (m + X_{vr})vr + (mx_G + X_{rr})r^2 + X_{\delta\delta}\delta^2 + X_{wind} + X_{waves} \quad (7)$$

$$(m - Y_{\dot{v}})\dot{v} + (mX_G - Y_{\dot{r}})\dot{r} = Y_{\delta}\delta + V_{sway} \quad (8)$$

$$(mX_G - N_{\dot{v}})\dot{v} + (I_z - N_{\dot{r}})\dot{r} = N_{\delta}\delta + N_{yaw} \quad (9)$$

From the equations (7 – 8) they are formed into *state space* \dot{u}, \dot{v} dan \dot{r} , so that:

Surge

$$\dot{u} = T_1((1-t)X_{prop} + U_{surge}) \quad (10)$$

Sway

$$\dot{v} = T_2(Y_{\delta}\delta_1 + V_{sway}) + T_3(N_{\delta}\delta_1 + N_{yaw}) \quad (11)$$

Yaw

$$\dot{r} = T_4(Y_{\delta}\delta_2 + V_{sway}) + T_5(N_{\delta}\delta_2 + N_{yaw}) \quad (12)$$

The expected linear model is obtained as follows:

$$\begin{aligned} \dot{\bar{x}}(t) &= A \bar{x}(t) + Bu(t) \\ \bar{y}(t) &= Cx(t) + Du(t) \end{aligned}$$

To determine $\bar{x}(t)$, the matrix of Jacobi is formed as follows:

$$J_{x1} = \begin{bmatrix} \frac{\partial \Sigma_X}{\partial u} & \frac{\partial \Sigma_X}{\partial v} & \frac{\partial \Sigma_X}{\partial r} \\ \frac{\partial \Sigma_Y}{\partial u} & \frac{\partial \Sigma_Y}{\partial v} & \frac{\partial \Sigma_Y}{\partial r} \\ \frac{\partial \Sigma_N}{\partial u} & \frac{\partial \Sigma_N}{\partial v} & \frac{\partial \Sigma_N}{\partial r} \end{bmatrix} \quad (13)$$

From the above differential derivation, the following is obtained.

$$A = J_{x2} = \begin{bmatrix} T_1 & 0 & 0 \\ 0 & T_2 & T_3 \\ 0 & T_4 & T_5 \end{bmatrix} J_{x1} \quad (14)$$

Then J_{x2} is obtained as follows.

$$A = J_{x2} = \begin{bmatrix} a_{11} & a_{12} & a_{13} \\ b_{21} & b_{22} & b_{23} \\ c_{31} & c_{32} & c_{33} \end{bmatrix} \quad (15)$$

In which,

$$\begin{aligned} a_{11} &= T_1 2\bar{u}X_{|u|u} \\ a_{12} &= T_1 \bar{r}(m + X_{vr}) \\ a_{13} &= T_1((m + X_{vr})\bar{v} + 2\bar{r}(mX_G + X_{rr})) \\ b_{21} &= T_2(-\bar{r}(m - Y_{ur}) + Y_{uv}\bar{v}) \\ &\quad + T_3(-\bar{r}(mX_G - N_{ur}) + \bar{v}N_{uv}) \\ b_{22} &= T_2(\bar{u}Y_{uv} + 2\bar{v}Y_{|v|v} + \bar{r}Y_{|v|r}) + T_3(\\ &\quad + 2\bar{v}N_{|v|v} + \bar{r}N_{|v|r}) \\ b_{23} &= T_2(-\bar{u}(m - Y_{ur}) + \bar{v}Y_{|v|r}) \\ &\quad + T_3(-\bar{u}(mX_G - N_{ur}) \\ &\quad + \bar{v}N_{|v|r}) \\ c_{31} &= T_4(-\bar{r}(m - Y_{ur}) + Y_{uv}\bar{v}) \\ &\quad + T_5(-\bar{r}(mX_G - N_{ur}) + \bar{v}N_{uv}) \\ c_{32} &= T_4(\bar{u}Y_{uv} + 2\bar{v}Y_{|v|v} + \bar{r}Y_{|v|r}) \\ &\quad + T_5(\bar{u}N_{uv} \\ &\quad + 2\bar{v}N_{|v|v} \\ &\quad + \bar{r}N_{|v|r}) \\ c_{33} &= T_4(-\bar{u}(m - Y_{ur}) + \bar{v}Y_{|v|r}) \\ &\quad + T_5(-\bar{u}(mX_G - N_{ur}) \\ &\quad + \bar{v}N_{|v|r}) \end{aligned}$$

Then, for the Jacobi Matrixes Control, partial derivation is done as follows.

$$J_{u1} = \begin{bmatrix} \frac{\partial \Sigma_X}{\partial X_{prop}} & \frac{\partial \Sigma_X}{\partial \delta} & \frac{\partial \Sigma_X}{\partial \delta} \\ \frac{\partial \Sigma_Y}{\partial X_{prop}} & \frac{\partial \Sigma_Y}{\partial \delta} & \frac{\partial \Sigma_Y}{\partial \delta} \\ \frac{\partial \Sigma_N}{\partial X_{prop}} & \frac{\partial \Sigma_N}{\partial \delta} & \frac{\partial \Sigma_N}{\partial \delta} \end{bmatrix} \quad (16)$$

Thus, the Jacobi Matrixes Control is as follows.

$$B = J_{u2} = \begin{bmatrix} T_1 & 0 & 0 \\ 0 & T_2 & T_3 \\ 0 & T_4 & T_5 \end{bmatrix} J_{u1} \quad (17)$$

$$B = J_{u2} = \begin{bmatrix} A_{11} & 0 & 0 \\ 0 & B_{22} & B_{23} \\ 0 & C_{32} & C_{33} \end{bmatrix} \quad (18)$$

In which,

$$\begin{aligned} A_{11} &= T_1(1-h) \\ B_{22} &= T_2Y_\delta + T_3N_\delta \\ B_{23} &= T_2Y_\delta + T_3N_\delta \\ C_{32} &= T_4Y_\delta + T_5N_\delta \\ C_{33} &= T_4Y_\delta + T_5N_\delta \end{aligned}$$

So that the result of the linearization from nonlinear model is as follows.

$$\begin{bmatrix} \dot{u} \\ \dot{v} \\ \dot{r} \end{bmatrix} = J_{x2} \begin{bmatrix} u \\ v \\ r \end{bmatrix} + J_{u2} \begin{bmatrix} X_{prop} \\ \delta \\ \delta \end{bmatrix} \quad (19)$$

$$\begin{bmatrix} \dot{u} \\ \dot{v} \\ \dot{r} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} & a_{13} \\ b_{21} & b_{22} & b_{23} \\ c_{31} & c_{32} & c_{33} \end{bmatrix} \begin{bmatrix} u \\ v \\ r \end{bmatrix} + \begin{bmatrix} A_{11} & 0 & 0 \\ 0 & B_{22} & B_{23} \\ 0 & C_{32} & C_{33} \end{bmatrix} \begin{bmatrix} X_{prop} \\ \delta \\ \delta \end{bmatrix} \quad (20)$$

From equation (19) to distinguish sway and yaw control motion so δ will be defined δ_1 and δ_2 for yaw

$$\begin{aligned} \dot{u} &= a_{11}u + a_{12}v + a_{13}r + A_{11}X_{prop} \\ \dot{v} &= b_{21}u + b_{22}v + b_{23}r + B_{22}\delta_1 + B_{23}\delta_1 \\ \dot{r} &= c_{31}u + c_{32}v + c_{33}r + C_{32}\delta_2 + C_{33}\delta_2 \end{aligned}$$

To determine $y(t)$ can be taken C as indentity matrix and $D = 0$.

3. Controllability and Observability

The system is said to be controllable if the matrix control rank is the same as the dimensions of the controllability matrix system that is formed from matrix A and matrix B. The controllability matrix is as follows:

$$Controlable = (B|AB|A^2B|...|A^{n-1}B)$$

The dimensions of the system is $n = 3$, so that it is

$$Controlable = (B|AB|A^2B|A^2B) = 3$$

So, the system is controllable because it has $rank = 3$

The system is said to be controllable if its observability rank has the same dimension as the system does. The observability matrix is formed of matrix A and matrix C, in which the observability matrix is as follows.

$$Observable = \begin{pmatrix} C \\ CA \\ CA^2 \\ \vdots \\ CA^{n-1} \end{pmatrix}$$

The dimensions of the system is $n = 3$, so that it is

$$Observable = \begin{pmatrix} C \\ CA \\ CA^2 \end{pmatrix}$$

So that the system is observable because it has $rank = 3$

4. CONCLUSION

Based on the Jacobian analysis, the controllability and observability of the Turistant ASV system is confirmed. And, the linearization of nonlinear ASV system can produce controllable and observable linear ASV system. Then, after the nature of the controllability and observability of the linear system of ASV, the model can be applied to navigation and guidance control system

5. REFERENCES

- [1]. Herlambang, T., Nurhadi H and Subchan, 2014. Preliminary Numerical Study on Designing Navigation and

- Stability Control Systems for ITS AUV, Applied Mechanics and Materials Vol. 493 (2014) pp 420-425 Trans Tech Publications, Switzerland.
- [2]. Herlambang, T., Djatmiko E.B and Nurhadi H., 2015, "Navigation and Guidance Control System of AUV with Trajectory Estimation of Linear Modelling", *Proc. of International Conference on Advance Mechatronics, Intelligent Manufactre, and Industrial Automation, IEEE* , ICAMIMIA 2015,Surabaya, Indonesia, pp. 184-187, Oct 15 – 17.
- [3]. Herlambang, T., Djatmiko E.B and Nurhadi H., 2015, "Ensemble Kalman Filter with a Square Root Scheme (EnKF-SR) for Trajectory Estimation of AUV SEGOROGENI ITS", *International Review of Mechanical Engineering IREME Journal*, Vol. 9, No. 6. Pp. 553-560, ISSN 1970 – 8734. Nov.
- [4]. Oktafianto, K., Herlambang T., Mardijah, Nurhadi H., 2015, "Design of Autonomous Underwater Vehcle Motion Control Using Sliding Mode Control Method", *International Conference on Advance Mechatronics, Intelligent Manufactre, and Industrial Automation (ICAMIMIA)-IEEE Surabaya Indonesia*, 15 – 16 Oktober 2015.
- [5]. Fossen, T.I. 1994. Guidance and Control of Ocean Vehicles. Hoboken :Wiley.

Optimization of Touristant ASV with Jacobian Approach

ORIGINALITY REPORT

14%

SIMILARITY INDEX

11%

INTERNET SOURCES

8%

PUBLICATIONS

9%

STUDENT PAPERS

PRIMARY SOURCES

1	repository.its.ac.id Internet Source	3%
2	Teguh Herlambang, Subchan Subchan, Hendro Nurhadi. "Design of Motion Control Using Proportional Integral Derivative for UNUSAITS AUV", International Review of Mechanical Engineering (IREME), 2018 Publication	3%
3	Teguh Herlambang, Subchan, Hendro Nurhadi. "Estimation of UNUSAITS AUV Position of Motion Using Extended Kalman Filter (EKF)", 2019 International Conference on Advanced Mechatronics, Intelligent Manufacture and Industrial Automation (ICAMIMIA), 2019 Publication	3%
4	Submitted to School of Business and Management ITB Student Paper	3%
5	archive.org Internet Source	2%



Exclude quotes On

Exclude matches < 2%

Exclude bibliography On